



Airport Information

The Provo Airport is served by two runways. Runway 13/31 is 8,600 feet long and 150 wide and is of asphalt construction. It has a porous friction course surface, and rated pavement strength of 65,000 pounds single wheel gear (SWG); 85,000 pounds dual wheel gear (DWG); 140,000 pounds tandem gear (DTG) loading.

Runway 13/31 is equipped with a high, low and medium intensity runway lighting system and served by a parallel taxiway system. A precision instrument landing system (ILS) is installed on runway 13, and visual landing aids include a PAPI-4 on Runway 13 and a PAPI-2 on runway 31.

Runway 18/36 is 6,602 feet long by 150 feet wide and is of asphalt construction. It is rated for 50,000 pounds SWG; 70,000 pounds DWG, and 110,000 pounds DTG. This runway has medium intensity lighting and PAPI-2 units on each runway end. Connecting taxiways link the runway to the apron areas.

The airport's terminal area is located on the east side of the airfield complex, and is comprised of fixed base operator facilities, hangars, T-hangars, tie downs, aircraft aprons, aircraft rescue and fire fighting facilities, as well as other miscellaneous structures, offering a complete line of aviation services.

Elevation: 4497

CTAF: 125.3

Ground: 119.4

AWOS: 135.17, 801-373-9782

ATCT Hours of Operation: 7:00AM – 9:00PM local time