

# Erosion Control and Cement Washout

- › Protect soil piles with an approved BMP method.
- › Protect (on-site) storm drain inlets and around the project with an approved BMP.
- › At the end of each work day, sweep or scrape up any soil that was tracked onto the road.
- › By the end of the next work day after a storm, clean up any soil that may have been washed off-site.
- › Inspect remove sediment deposits.
- › Secure bags of cement after they are open. Be sure to keep windblown cement powder away from gutters, storm drains and runoff.
- › Place concrete washout in an approved designated washout area.
- › Concrete can be washed out in a secure plastic lined area.

## Contact Information

To report a spill during regular business hours Monday - Thursday 7a - 6p contact: Provo City Storm Water at 801 852 6743.

To report a spill after business hours contact Provo City Customer Service by dialing 311.

For general storm water program information contact the Storm Water Quality Program Manager at 801 852 6783, check out our website [provo.org/pubworks](http://provo.org/pubworks). Our offices are located at 1377 S 350 E, Provo.

For waste disposal questions contact: South Utah Valley Solid Waste District at 801 489 3027 or visit the following website: [suvswd.org/whattodo.html](http://suvswd.org/whattodo.html).

Anyone caught discharging anything but rain into the storm drain is subject to penalties and/or fines, plus the cost of clean up.

Please help stop storm water pollution at the source.

